

SCHEMA TECNICA
DATA SHEET

ARTICOLO ITEM	SOLANO FR	
COMPOSIZIONE COMPOSITION	98% PVC – 2% PU	
COMPOSIZIONE RETRO BACKING	100% PL	
PESO gr/m ² WEIGHT gr/m ²	750 ± 5%	
RESISTENZA ABRASIONE ABRASION RESISTANCE	> 200.000 rubs	ISO 12947-2
SOLIDITA' COLORE ALLO SFREGAMENTO COLOR FASTNESS FOR RUBBING	≥ 5	ISO 105 X12 (Grey Scale)
RESISTENZA UV UV RESISTANCE	1000 hours (Blue Wool Scale) ≥6/7	
RESISTENZA AL FUOCO FIRE RESISTANCE	BS 5852 Part 1 Ignition Source 0,1 (Cigarette & Match)	
	EN 1021 Part 1 and 2	
	BS 7176 Low Hazard	
	IMO FTP Code Annex 1 Part 8	
	DIN 4102 B2	
	French NFP 92 503 (M2)	
	US: CAL TB 117-2013, Section E	
	AT: ÖNORM B 3825, Gruppe 1	
	AT: ÖNORM A 3800 Teil 1	
	FMVSS 302 (FR Standart of Motor Vehicles)	
	*Optional DIN 4102 B1 and French NFP 92 503 (M1)	
	MOQ 500 mt/color	
ANTIBATTERICO ANTIBACTERIAL	ISO 22196 Measurement of Antibacterial Activity	
ANTIMICROBICO ANTIMICROBIEL	AATCC 147 Antibacterial Activity Assessment	
ANTIMICOTICO	ASTM G 21 Standard Practice for Determining	

ANTIFUNGAL	Resistance of Synthetic Polymeric Materials to Fungi
PULIZIA CON CANDEGGINA BLEACH CLANABLE	ISO 105 E03 color change 4 for dilution factor 1:4 chlorine solution (Grey Scale) ≥4
RESISTENZA ALL'ACQUA WATERPROOF	BS 3424 Part 26 > 1 meter
SICUREZZA DEI GIOCATTOLI SAFETY OF TOYS	EN 71-3 Safety of toys part 3: The migration of Some Elements
RESISTENZA ALL'UREA UREA RESISTANCE	BS 3424 Part 19 After 24 hours , No Significant Deterioration
FACILE DA PULIRE EASY CLEAN	Pulisci con un panno umido usando acqua e sapone o usa uno shampoo per tappezzeria brevettato. Per una pulizia più profonda utilizzare candeggina Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. For deeper cleaning use bleach
SOSTENIBILITÀ SUSTAINABILITY	STANDARD 100 by OEKO-TEX® Annex 4 product class IV Edition NSO-NAP 7:2018 Vegan & Vejetarian Standard