

SCHEMA TECNICA
DATA SHEET

ARTICOLO ITEM	LIBECCIO FR-5	
COMPOSIZIONE COMPOSITION	98% PVC – 2% PU	
COMPOSIZIONE RETRO BACKING	100% VI	
PESO gr/m ² WEIGHT gr/m ²	750 ± 5%	
RESISTENZA ABRASIONE ABRASION RESISTANCE	> 100.000 rubs	ISO 12947-2
SOLIDITA' COLORE ALLO SFREGAMENTO COLOR FASTNESS FOR RUBBING	≥ 5	ISO 105 X12 (Grey Scale)
RESISTENZA UV UV RESISTANCE	1000 hours (Blue Wool Scale) ≥6/7	
RESISTENZA AL FUOCO FIRE RESISTANCE	BS 5852 Part 1 Ignition Source 0,1 (Cigarette & Match)	
	EN 1021 part 1 and 2	
	BS 5852 Part 1 Ignition Source 5	
	BS 7176 Medium Hazard	
	DIN 4102 B1	
	DIN 4102 B2	
	French NFP 92 503 (M1)	
	French NFP 92 503 (M2)	
	UNI 9175 CLASSE 1M	
	IMO FTP Code Annex 1 Part 5	
	FMVSS 302 (FR Standart of Motor Vehicles	
	ECE R 118 ANNEX 6,7,8	
	US: CAL TB 117-2013, Section E	
	US: FAR 25/853	
	AT: ÖNORM B 3825, Gruppe 1	
	AT: ÖNORM A 3800 Teil 1	

ANTIBATTERICO ANTIBACTERIAL	ISO 22196 Measurement of Antibacterial Activity
ANTIMICROBICO ANTIMICROBIAL	AATCC 147 Antibacterial Activity Assessment
ANTIMICOTICO ANTIFUNGAL	ASTM G 21 Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi
PULIZIA CON CANDEGGINA BLEACH CLANABLE	ISO 105 E03 color change 4 for dilution factor 1:4 chlorine solution (Grey Scale) ≥ 4
RESISTENZA ALL'ACQUA WATERPROOF	BS 3424 Part 26 > 1 meter
SICUREZZA DEI GIOCATTOLI SAFETY OF TOYS	EN 71-3 Safety of toys part 3: The migration of Some Elements
MIGRAZIONE MIGRATION	0.1 % by mass of the plasticized material I in toys and childcare articles
RESISTENZA ALL'UREA UREA RESISTANCE	BS 3424 Part 19 After 24 hours , No Significant Deterioration
FACILE DA PULIRE EASY CLEAN	Pulisci con un panno umido usando acqua e sapone o usa uno shampoo per tappezzeria brevettato. Per una pulizia più profonda utilizzare candeggina Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. For deeper cleaning use bleach